MATERIAL SAFETY DATA SHEET FOR COATINGS, RESINS, AND RELATED MATERIALS DATE OF PREPARATION - 01-03-2010 Prepared by: Compliance Dept.

SECTION I - PRODUCT IDENTIFICATION

MANUFACTURER: DISTRIBUTOR:	Munro Products 9150 Clarence Center Road Clarence Center, NY 14032
INFORMATION:	716/741-9450
EMERGENCY:	CHEMTREC®1-800-424-9300
PRODUCT CLASS:	INDUSTRIAL MAINTENANCE
TRADE NAME:	BathWorks Revitalizing Cream
CODE:	BW-315

SECTION 2: INGREDIENTS

Ingredient	C.A.S. No.	<u>% by Wt</u>
WATER	7732-18-5	40 - 70
ALUMINUM OXIDE	1344-28-1	7 - 13
HYDROTREATED LIGHT PETROLEUM DISTILLATES	64742-47-8	7 - 13
DECAMETHYLCYCLOPENTASILOXANE	541-02-6	< 12
DODECAMETHYLCYCLOHEXASILOXANE	540-97-6	< 8
HYDROTREATED HEAVY NAPHTHA PETROLEUM	64742-48-9	3 - 7
GLYCERIN	56-81-5	1 - 5
SOLVENT-REFINED HEAVY PARAFFINIC PETROLEUM DISTILLATES	64741-88-4	0.5 - 1.5
POLY(OXY-1,2-ETHANEDIYL),.ALPHAUNDECYLOMEGAHYDROXY-	34398-01-1	0.1 - 1
DISTILLATES, PETROLEUM, SOLVENT-REFINED LIGHT PARAFFINIC	64741-89-5	< 0.5
FORMALDEHYDE	50-00-0	< 0.02

SECTION 3: HAZARDS IDENTIFICATION

3.1 EMERGENCY OVERVIEW

Specific Physical Form: Emulsion Odor, Color, Grade: Slight solvent odor, white emulsion General Physical Form: Liquid Immediate health, physical, and environmental hazards: Combustible liquid and vapor. Closed containers exposed to heat from fire may build pressure

May cause target organ effects. Contains a chemical or chemicals which can cause cancer.

3.2 POTENTIAL HEALTH EFFECTS

Eye Contact:

Mild Eye Irritation: Signs/symptoms may include redness, pain, and tearing.

Skin Contact:

Moderate Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

Inhalation:

Intentional concentration and inhalation may be harmful or fatal.

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May be absorbed following inhalation and cause target organ effects.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May be absorbed following ingestion and cause target organ effects.

Target Organ Effects:

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Ingredient FORMALDEHYDE

FORMALDEHYDE FORMALDEHYDE <u>C.A.S. No.</u> 50-00-0 50-00-0

50-00-0

Class Description Grp. 1: Carcinogenic to humans Anticipated human carcinogen Cancer hazard <u>Regulation</u> International Agency for Research on Cancer

National Toxicology Program Carcinogens OSHA Carcinogens

SECTION 4: FIRST AID MEASURES

4.1 FIRST AID PROCEDURES

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

Eye Contact: Flush eyes with large amounts of water. If signs/symptoms persist, get medical attention.

Skin Contact: Remove contaminated clothing and shoes. Immediately flush skin with large amounts of water. Get medical attention. Wash contaminated clothing and clean shoes before reuse.

Inhalation: Remove person to fresh air. If signs/symptoms develop, get medical attention.

If Swallowed: Do not induce vomiting unless instructed to do so by medical personnel. Give victim two glasses of water. Never give anything by mouth to an unconscious person. Get medical attention.

SECTION 5: FIRE FIGHTING MEASURES

5.1 FLAMMABLE PROPERTIES

Autoignition temperature Flash Point Flammable Limits - LEL Flammable Limits - UEL No Data Available 188 °F [Test Method: Closed Cup] No Data Available No Data Available

5.2 EXTINGUISHING MEDIA

Use fire extinguishers with class B extinguishing agents (e.g., dry chemical, carbon dioxide).

5.3 PROTECTION OF FIRE FIGHTERS

Special Fire Fighting Procedures: Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

Unusual Fire and Explosion Hazards: Combustible liquid and vapor. Closed containers exposed to heat from fire may build pressure and explode. Vapors may travel long distances along the ground or floor to an ignition source and flash back.

Note: See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition information.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions

Evacuate unprotected and untrained personnel from hazard area. The spill should be cleaned up by qualified personnel. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode.

Environmental procedures

For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water. Place in a closed container approved for transportation by appropriate authorities. Dispose of collected material as soon as possible.

Clean-up methods

Observe precautions from other sections. Call 716-741-9450 for more information on handling and managing the spill. Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Collect as much of the spilled material as possible using non-sparking tools. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and MSDS.

In the event of a release of this material, the user should determine if the release qualifies as reportable according to local, state, and federal regulations.

SECTION 7: HANDLING AND STORAGE

7.1 HANDLING

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water. Keep away from heat, sparks, open flame, pilot lights and other sources of ignition. No smoking while handling this material. Avoid breathing of vapors, mists or spray. Avoid skin contact. Keep out of the reach of children. Avoid contact with oxidizing agents. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below Occupational Exposure Limits. If ventilation is not adequate, use respiratory protection equipment. Avoid eye contact.

7.2 STORAGE

Store away from acids. Store away from heat. Store out of direct sunlight. Store away from oxidizing agents.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 ENGINEERING CONTROLS

Use with appropriate local exhaust ventilation. Use in an enclosed process area is recommended. Provide ventilation adequate to control dust concentrations below recommended exposure limits and/or control dust.

8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)

8.2.1 Eye/Face Protection

Avoid eye contact. The following eye protection(s) are recommended: Safety Glasses with side shields Indirect Vented Goggles

8.2.2 Skin Protection

Avoid skin contact.

Select and use gloves and/or protective clothing to prevent skin contact based on the results of an exposure assessment. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible materials. Gloves made from the following material(s) are recommended: Nitrile Rubber

8.2.3 Respiratory Protection

Avoid breathing of vapors, mists or spray.

Select one of the following NIOSH approved respirators based on airborne concentration of contaminants and in accordance with OSHA regulations: Half facepiece or fullface air-purifying respirator with organic vapor cartridges and P95 particulate prefilters . Consult the current 3M Respiratory Selection Guide for additional information or call 1-800-243-4630 for 3M technical assistance.

8.2.4 Prevention of Swallowing

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water.

8.3 EXPOSURE GUIDELINES

<u>Ingredient</u>	<u>Authority</u>	Type	<u>Limit</u>	Additional Information
ALUMINUM OXIDE	CMRG	TWA	1 fiber/cc	
ALUMINUM OXIDE	OSHA	TWA, respirable	5 mg/m3	
		fraction		
ALUMINUM OXIDE	OSHA	TWA, as total dust	15 mg/m3	
DECAMETHYLCYCLOPENTASILOXANE	CMRG	TWA	10 ppm	
FORMALDEHYDE	ACGIH	CEIL	0.3 ppm	Sensitizer
FORMALDEHYDE	CMRG	TWA	0.5 ppm	
FORMALDEHYDE	OSHA	TWA	0.75 ppm	29 CFR 1910.1048
FORMALDEHYDE	OSHA	STEL	2 ppm	29 CFR 1910.1048
GLYCERIN	ACGIH	TWA, as mist	10 mg/m3	
GLYCERIN	OSHA	TWA, respirable	5 mg/m3	
		fraction		
GLYCERIN	OSHA	TWA, as total dust	15 mg/m3	
HYDROTREATED HEAVY NAPHTHA	3M	TWA	100 ppm	
PETROLEUM				
HYDROTREATED HEAVY NAPHTHA	CMRG	TWA	300 ppm	
PETROLEUM				
HYDROTREATED LIGHT PETROLEUM	CMRG	TWA	300 ppm	
DISTILLATES				
SOLVENT-REFINED HEAVY PARAFFINIC	CMRG	TWA	5 mg/m3	
PETROLEUM DISTILLATES				

SOURCE OF EXPOSURE LIMIT DATA:

ACGIH: American Conference of Governmental Industrial Hygienists CMRG: Chemical Manufacturer Recommended Guideline OSHA: Occupational Safety and Health Administration AIHA: American Industrial Hygiene Association Workplace Environmental Exposure Level (WEEL)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Specific Physical Form: Odor, Color, Grade: General Physical Form: Autoignition temperature Flash Point Flammable Limits - LEL Flammable Limits - UEL Boiling point Density Vapor Density

Vapor Pressure

Emulsion Slight solvent odor, white emulsion Liquid *elbaliavA ataD on elbaliavA ataD on elbaliavA ataD on elbaliavA ataD on Passer ataD on provide ataD on provide ataD on elbaliavA ataD on elbaliavA ataD on elbaliavA ataD on elbaliavA ataD on provide at*

elbaliavA ataD oN

Specific Gravity pH Melting point

Solubility in Water Evaporation rate Hazardous Air Pollutants Volatile Organic Compounds Volatile Organic Compounds Volatile Organic Compounds Kow - Oct/Water partition coef VOC Less H2O & Exempt Solvents Viscosity 1 [1=R3TAW : dtS feR] 1 8

elbaliavA ataD oN

Negligible No Gata Availadle 0.0191 % weight [Test Methob: Calculated] 151 g/l [Test Methob: calculated SCAQMD rule 443.1] 1.25 lb/gal [Test Methob: calculated SCAQMD rule 443.1] 15.0 % weight [Test Methob: calculated per CARB title 2] No Gata Availadle 3.17 lb/gal [Test Methob: calculated SCAQMD rule 443.1] 22000 - 28000 centipoise

SECTION 10: STABILITY AND REACTIVITY

Stability: Stable.

Materials and Conditions to Avoid: 10.1 Conditions to avoid None known

10.2 Materials to avoid None known

Hazardous Polymerization: Hazardous polymerization will not occur.

Hazardous Decomposition or By-Products

Substance Formaldehyde Carbon monoxide Carbon dioxide Oxides of Nitrogen <u>Condition</u> During Combustion During Combustion During Combustion During Combustion

SECTION 11: TOXICOLOGICAL INFORMATION

Please contact the address listed on the first page of the MSDS for Toxicological Information on this material and/or its components.

SECTION 12: ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION

Not determined.

CHEMICAL FATE INFORMATION

Not determined.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Method: Incinerate in an industrial or commercial facility. As a disposal alternative, dispose of waste product in a facility permitted to accept chemical waste.

EPA Hazardous Waste Number (RCRA): Not regulated

Since regulations vary, consult applicable regulations or authorities before disposal.

SECTION 14:TRANSPORT INFORMATION

ID Number(s):

LB-K000-1068-0, LB-K000-1068-1, LB-K100-0349-7, 60-4100-0937-1, 60-4100-0938-9, 60-4400-9540-8, 60-4400-9967-3, 60-4550-5283-1, 60-4550-5283-1, 60-4550-5283-1, 60-4550-5283-1, 60-4550-5425-8, 60-9801-0936-1

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: REGULATORY INFORMATION

US FEDERAL REGULATIONS

Contact 3M for more information.

311/312 Hazard Categories:

Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - No

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

Ingredient	C.A.S. No	<u>% by Wt</u>
ALUMINUM OXIDE	1344-28-1	7 - 13

STATE REGULATIONS

Contact 3M for more information.

CALIFORNIA PROPOSITION 65

Ingredient FORMALDEHYDE <u>C.A.S. No.</u> 50-00-0 Classification **Carcinogen ** WARNING: contains a chemical which can cause cancer.

CHEMICAL INVENTORIES

The components of this product are in compliance with the chemical notification requirements of TSCA.

All applicable chemical ingredients in this material are listed on the European Inventory of Existing Chemical Substances (EINECS), or are exempt polymers whose monomers are listed on EINECS.

Contact Tub Refinishing, Inc. for more information.

INTERNATIONAL REGULATIONS

Contact Tub Refinishing, Inc. for more information.

This MSDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: OTHER INFORMATION

NFPA Hazard Classification

Health: 1 Flammability: 2 Reactivity: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Revision Changes: Section 1: Product name was modified. Copyright was modified. Section 3: Potential effects from eve contact was modified.

- Section 3: Potential effects from inhalation information was modified.
- Section 5: Fire fighting procedures information was modified.
- Section 7: Handling information was modified.
- Section 7: Storage information was modified.
- Section 8: Engineering controls information was modified.
- Section 8: Eye/face protection information was modified.
- Section 8: Skin protection recommended gloves information was modified.
- Section 8: Respiratory protection recommended respirators information was modified.
- Section 3: Immediate other hazard(s) was modified.
- Section 14: Transportation legal text was modified.
- Page Heading: Product name was modified.
- Section 15: Inventories information was modified.
- Section 9: Density information was modified.

Section 9: Property description for optional properties was modified. Section 14: ID Number(s) Template 1 was modified. Section 2: Ingredient table was modified. Section 8: Exposure guidelines ingredient information was modified. Section 3: Carcinogenicity phrase was added. Section 15: EPCRA 313 information was added. Section 15: EPCRA 313 text was added. Section 3: Carcinogenicity table was added. Section 3: Carcinogenicity heading was added. Section 15: California proposition 65 ingredient information was added. Section 15: California proposition 65 heading was added. Section 15: California proposition 65 cancer warning was added. Section 6: Environmental procedures heading was added. Section 6: Personal precautions heading was added. Section 10.1 Conditions to avoid heading was added. Section 10.2 Materials to avoid heading was added. Section 6: Personal precautions information was added. Section 6: Environmental procedures information was added. Section 6: Methods for cleaning up information was added. Section 10: Materials to avoid physical property was added. Section 10: Conditions to avoid physical property was added. Section 6: Clean-up methods heading was added. Section 6: Release measures information was deleted. Section 6: Release measures heading was deleted. Section 10: Materials and conditions to avoid physical property was deleted. Section 8: Exposure guidelines legend was deleted.

NON WARRANTY: The information presented herein, while not guaranteed, is to the best of our knowledge true and accurate. Non warranty or guarantee expressed or implied is made regarding the performance of any product since the manner of use is beyond our control. No suggestion for product use nor anything contained herein shall be construed as a recommendation for its use in infringement of any existing patent, and Munro assumes no responsibility or liability for operations that do infringe any such patents.

TUB REFINISHING, INC. DBA MUNRO PRODUCTS