SAFETY DATA SHEET FOR COATINGS, RESINS, AND RELATED MATERIALS DATE OF PREPARATION - 01-01-2014 Prepared by: Compliance Dept.

SECTION I - PRODUCT IDENTIFICATION

MANUFACTURER: Munro Products

DISTRIBUTOR: 9150 Clarence Center Road

Clarence Center, NY 14032

INFORMATION: 716/741-9450

EMERGENCY: CHEMTREC® 1-800-424-9300

PRODUCT CLASS: RESIN ADHESIVE

TRADE NAME: Seal-Lok

CODE: SR1003

SECTION II - HAZARDOUS INGREDIENTS

COMMON NAME CHEMICAL NAME **OCCUPATIONAL** WEIGHT LEL VAPOR **EXPOSURE PRESSURE** LIMITS **TOLUENE** 1.3 100 ppm 375 mg/m3 75 22/20 C (TWA-ACGIH) 200 ppm (TWA-OSHA) 1-BUTANOL <5 1.4 4.2/20 C 50 ppm 150 mg/m3 Ceiling (TWA-ACGIH) 100 ppm 330 mg/m3 (TWA-OSHA) 2-BUTOXY FTHANOL 25 Mm 120 mg/m3 0.6/20 C (Skin) (Skin) (TWA-ACGIH) 50 mm 240mg/m3 (Skin) (Skin) ETHYL ALCOHOL 44/20 C <5 3.3 1900 mg/m3 1000 ppm

SECTION III - PHYSICAL DATA

VOLUME PERCENT VOLATILE: 90 BOILING RANGE: 165-256 F

(TWA-ACGIH & OSHA)

SOLUBLE: No EVAPORATION RATE: Slower, than Ether

WEIGHT PER GALLON: 7.4 lbs VAPOR DENSITY: Heavier than Air

VOC OF MATERIAL: 6.79 lb/gal, 813 g/l

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 35 F TCC LEL: 1.1

EXTINGUISHING MEDIA: Foam, Alcohol Foam, CO2, Dry Chemical, Water Fog, and Halon 1211.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Keep containers tightly closed. Isolate from heat,

electrical equipment, sparks and open flame. Closed containers may explode when exposed to extreme heat

SPECIAL FIREFIGHTING PROCEDURES AND PRECAUTIONS: Full protective equipment, including self-contained breathing apparatus, should be used. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build up and possible auto ignition or explosion.

SECTION V - HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE (ACUTE)

Irritation of the respiratory tract or central nervous system depression characterized by the following progressive steps: headache, dizziness, staggering gait, confusion, unconsciousness or coma.

SKIN AND EYES: Irritant.

ADDITIONAL EFFECTS OF OVEREXPOSURE (CHRONIC):

Permanent central nervous system changes can occur due to solvent overexposure. May cause system, liver, skin, eves.

MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE:

Respiratory allergies. Chronic

diseases of the central nervous system, liver, skin, eyes.

PRIMARY ROUTES OF ENTRY: Dermal, Inhalation, Ingestion.

FIRST AID:

INHALATION: Move person to fresh air. Restore breathing. Treat systematically. Consult a physician.

EYES: Flush immediately with large amounts of water for at least 15 minutes. Consult a physician.

SKIN: Wash affected skin areas with soap and water. Remove contaminated clothing. Consult a physician if irritation persists.

INGESTION: Drink one or two glasses of water to dilute. Do not induce vomiting. Consult a physician or poison control center immediately.

SECTION VI - REACTIVITY DATA

HAZARDOUS POLYMERIZATION: Will not occur. STABILITY: Stable

INCOMPATIBILITY (Materials to avoid): Strong acids and bases, halogens, ammonia.

CONDITIONS TO AVOID: High Temperatures.

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Eliminate all ignition sources (flares, flames including pilot lights, electrical sparks). Avoid breathing vapors. Use self-contained breathing equipment. Ventilate area. Continue and remove with inert absorbent material and non-sparking tool.

DISPOSAL OF CONTENTS: Disposal should be done in accordance with Federal, State and Local regulations. Use licensed hazardous waste disposal concern.

SECTION VIII - PROTECTIVE EQUIPMENT

VENTILATION: Sufficient ventilation, in pattern and volume, should be provided to keep the air contaminant concentration below applicable exposure limits. Heavy solvent vapors should be removed from the lower levels of work area, and all ignition sources (non-explosion proof equipment) should be eliminated if flammable/air mixtures will be encountered.

RESPIRATORY PROTECTION: Use approved chemical/mechanical filters designed to remove a combination of particulates and organic vapor in open and restricted ventilation areas. Use approved airline type respirators or hoods in confined area.

PROTECTIVE GLOVES: Use neoprene or rubber gloves to prevent skin contact.

OTHER PROTECTIVE EQUIPMENT: Use protective cream if skin contact is likely. Use disposable or impervious clothing if work clothing contaminations likely.

HYGIENIC PRACTICES: Wash hands before eating, smoking or using the wash room. Do not smoke in any chemical handling storage area. Food or beverages should not be consumed anywhere this product is handled or stored.

SECTION IX - SPECIAL PRECAUTIONS AND ADDITIONAL COMMENTS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Do not store or use near heat or open flame. Store drum out of sun and away from heat. Keep closure tight and container upright to prevent leakage.

OTHER PRECAUTIONS: Drums of this material should be grounded and bonded when pouring. Do not puncture, drag or slide container. Empty drums should be reused. Do not get in eyes. Avoid skin contact. Prevent prolonged or repeated breathing of vapor or spray mists. Do not weld or flame-cut an empty drum.

NON WARRANTY: The information presented herein, while not guaranteed, is to the best of our knowledge true and accurate. Non warranty or guarantee expressed or implied is made regarding the performance of any product since the manner of use is beyond our control. No suggestion for product use nor anything contained herein shall be construed as a recommendation for its use in infringement of any existing patent, and Munro assumes no responsibility or liability for operations that do infringe any such patents.

TUB REFINISHING, INC. DBA MUNRO PRODUCTS