SAFETY DATA SHEET FOR COATINGS, RESINS, AND RELATED MATERIALS DATE OF PREPARATION - 01-01-2014 Prepared by: Compliance Dept. SECTION I - PRODUCT IDENTIFICATION		SECTION V - HEALTH HAZARD DATA			
		HEALTH HAZARDS (ACUTE AND CHRONIC)     SKIN & EYE   - Can cause slight ransient eye irritation. Corneal injury is unlikely. Irrigate immediately with water for 15 minutes.     INHALATION   - Remove to fresh air. If symptoms persist contact a physician.			
			MANUFACTURER: DISTRIBUTOR:	Munro Products 9150 Clarence Center Road Clarence Center, NY 14032	ORAL INGESTION - Single oral does toxivity is low. No hazards anticipated from ingestion incidental to industrial exposure.
			INFORMATION: EMERGENCY:	716/741-9450 CHEMTREC <sup>®</sup> 1-800-424-9300	SECTION VI - REACTIVITY DATA
STABILITY: Stable					
PRODUCT CLASS:		INCOMPATIBILITY - Base acids, amines, oxidizing materials.			
TRADE NAME:	MODIFIED EPOXY Epoxy Seal XL	HAZARDOUS POLYMERIZATION: Will NOT occur.			
CODE:	M14000	CONDITIONS TO AVOID - Masses of more than 1 lb. of products plus an aliphatic amine will cause irreversible polymerization with considerable heat build up.			
SE	CTION II - HAZARDOUS INGREDIENTS				
COMMON NAME	CHEMICAL NAME	SECTION VII - SPILL OR LEAK PROCEDURES			
ORAL DERMAL	LC50	STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Remove all sources of ignition. Absorb with inert materials and dispose as per local, state and federal regulations.			
EPON 828		PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Store in closed, upright containers.			
Rat 11.4 Rat 1.2		OTHER PRECAUTIONS: Excess heating over long periods of time degrades resin.			
EPON 1002 Rat 30g/kg					
METHYLCTHYLKETONE Rat 3.300 Rabbit 8-10.00		SECTION VIII - PROTECTIVE EQUIPMENT			
XYLENE (I) 10ml/kg -5 ml/kg	sg (l) 6350 pp	RESPIRATORY PROTECTION - Should not be necessary.			
(I) 10ml/kg -5 ml/k BEETLE 216-8 Rat 790-4300 mg/kg		VENTILATION - Should be adequate.			
		PROTECTIVE GLOVES - Impervious gloves.			
		EYE PROTECTION - Safety splash goggles.			
SECTION III - PHYSICAL DATA		WORK/HYGIENIC PRACTICES - Practice good hygiene. Keep away from food and feed products.			
BOILING POINT: 75-85 C SPECIFIC GRAVITY: 1.16-1.18   VAPOR PRESSURE: NA MELTING POINT: NA		THE INFORMATION HEREIN RELATES TO THE PRODUCT NAMED AND IS BASED UPON			
		INFORMATION MUNRO PRODUCTS CONSIDERED TO BE ACCURATE. NO WARRANTY EXPRESSED OR IMPLIED IS INTENDED.			
VAPOR DENSITY: NA	EVAPORATION RATE: NA				
SOLUBILITY IN WATER:   NA     APPEARANCE AND ODOR:   Clear or colored viscous liquid in uncured form, aromatic.		NON WARRANTY The information presented herein, while not guaranteed, is to the best of our knowledge true and accurate. No warranty or guarantee expressed or implied is made regarding the performance of any product, since the manner of use is beyond our control. No suggestion for product use, nor anything contained herein, shall be construed as a recommendation for its use in infringement of any existing patent, and Munro assumes no responsibility or liability for operations that do infringe any such patents.			
			SECTION IV - FIRE AND EXPLOSION HAZARD DATA		
Flash Point: 485 F (252 C)			TUB REFINISHING, INC. DBA MUNRO PRODUCTS		
EXTINGUISHING MEDIA - Foam, CO2, Dry Chemical.					
SPECIAL FIRE FIGHTING PROCEDURES - NA					
UNUSUAL FIRE AND EXPLOSION	HAZARDS - None.				